

WIRE ROPE LANYARD ASSEMBLIES



Wire rope lanyard assemblies are used to attach quick release pins to a fixture or frame, to prevent the pins from being misplaced while they are not in use. All of the wire rope lanyard assemblies listed below are supplied with 7 x 7 stainless steel wire and are available either uncovered (bare cable) or covered. The vinyl covered assemblies are available in either clear, black or green. The 3/64" wire is covered to 1/16" diameter. The 1/16" wire is covered to 1/8" diameter. The rated break strength of the 3/64" wire is 270 pounds, and the 1/16" wire is 480 pounds. Cable assemblies using eyelets are rated at 30 pounds. All tabs and eyelets are manufactured from 300 series stainless steel. All cable sleeves are manufactured from zinc plated copper. In addition to the standard parts listed below, we can provide custom lanyards based on your exact requirements.

Loop / Rectangular Tab



Clear Part #	Black Part #	Green Part #	Uncovered Part #	Wire Diameter	Length	A
LCL-3-06-R20	LBK-3-06-R20	LGR-3-06-R20	LNC-3-06-R20	3/64	6	.20
LCL-3-08-R20	LBK-3-08-R20	LGR-3-08-R20	LNC-3-08-R20	3/64	8	.20
LCL-3-10-R20	LBK-3-10-R20	LGR-3-10-R20	LNC-3-10-R20	3/64	10	.20
LCL-3-12-R20	LBK-3-12-R20	LGR-3-12-R20	LNC-3-12-R20	3/64	12	.20
LCL-3-06-R28	LBK-3-06-R28	LGR-3-06-R28	LNC-3-06-R28	3/64	6	.28
LCL-3-08-R28	LBK-3-08-R28	LGR-3-08-R28	LNC-3-08-R28	3/64	8	.28
LCL-3-10-R28	LBK-3-10-R28	LGR-3-10-R28	LNC-3-10-R28	3/64	10	.28
LCL-3-12-R28	LBK-3-12-R28	LGR-3-12-R28	LNC-3-12-R28	3/64	12	.28
LCL-1-06-R20	LBK-1-06-R20	LGR-1-06-R20	LNC-1-06-R20	1/16	6	.20
LCL-1-08-R20	LBK-1-08-R20	LGR-1-08-R20	LNC-1-08-R20	1/16	8	.20
LCL-1-10-R20	LBK-1-10-R20	LGR-1-10-R20	LNC-1-10-R20	1/16	10	.20
LCL-1-12-R20	LBK-1-12-R20	LGR-1-12-R20	LNC-1-12-R20	1/16	12	.20
LCL-1-06-R28	LBK-1-06-R28	LGR-1-06-R28	LNC-1-06-R28	1/16	6	.28
LCL-1-08-R28	LBK-1-08-R28	LGR-1-08-R28	LNC-1-08-R28	1/16	8	.28
LCL-1-10-R28	LBK-1-10-R28	LGR-1-10-R28	LNC-1-10-R28	1/16	10	.28
LCL-1-12-R28	LBK-1-12-R28	LGR-1-12-R28	LNC-1-12-R28	1/16	12	.28

Loop / Loop



Clear Part #	Black Part #	Green Part #	Uncovered Part #	Wire Diameter	Length
LCL-3-06	LBK-3-06	LGR-3-06	LNC-3-06	3/64	6
LCL-3-08	LBK-3-08	LGR-3-08	LNC-3-08	3/64	8
LCL-3-10	LBK-3-10	LGR-3-10	LNC-3-10	3/64	10
LCL-3-12	LBK-3-12	LGR-3-12	LNC-3-12	3/64	12
LCL-1-06	LBK-1-06	LGR-1-06	LNC-1-06	1/16	6
LCL-1-08	LBK-1-08	LGR-1-08	LNC-1-08	1/16	8
LCL-1-10	LBK-1-10	LGR-1-10	LNC-1-10	1/16	10
LCL-1-12	LBK-1-12	LGR-1-12	LNC-1-12	1/16	12